


Features

- fLow gate charge
- f100% avalanche tested
- fImproved dv/dt capability
- fRoHS compliant
- fHalogen free package
- fJEDEC Qualification
- fImproved ESD performance



Device	Package	Marking	Remark
TMP8N60AZ / TMPF8N60AZ	TO-220 / TO-220F	TMP8N60AZ / TMPF8N60AZ	RoHS
TMP8N60AZG / TMPF8N60AZG	TO-220 / TO-220F	TMP8N60AZG / TMPF8N60AZG	







Absolute Maximum Ratings





Parameter	Symbol	TMP8N60AZ(G)	TMPF8N60AZ(G)	Unit	
Drain-Source Voltage	V_{DSS}	600		V	
Gate-Source Voltage	V_{GS}	30		V	
Continuous Drain Current	I_D	$T_C = 25$	7.5 *	A	
		$T_C = 100$	4.12 *	A	
Pulsed Drain Current (Note 1)	I_{DM}	30	30 *	A	
Single Pulse Avalanche Energy (Note 2)	E_{AS}	223		mJ	
Repetitive Avalanche Current (Note 1)	I_{AR}	7.5		A	
Repetitive Avalanche Energy (Note 1)	E_{AR}	12		mJ	
Power Dissipation	P_D	$T_C = 25$	120	39	W
		Derate above 25	0.96	0.31	W/
Peak Diode Recovery dv/dt (Note 3)	dv/dt	4.5		V/ns	
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55~150			
Maximum lead temperature for soldering purposes,	T_L	300			

* Limited only by maximum junction temperature


Thermal Characteristics

Parameter	Symbol	TMP8N60AZ(G)	TMPF8N60AZ(G)	Unit
Maximum Thermal resistance, Junction-to-Case	$R_{\theta JC}$	1.04	3.2	/W
Maximum Thermal resistance, Junction-to-Ambient	$R_{\theta JA}$	62.5	62.5	/W







TMP8N60AZ(G)




TMPF8N60AZ(G)




TMP8N60AZ(G)



TMPF8N60AZ(G)



TO-220AB-3L MECHANICAL DATA



	0.002"
-A-	0.05mm

SYMBOL	INCHES		MILLIMETERS		NOTES
	MIN.	MAX.	MIN.	MAX.	
A	0.170	0.180	4.32	4.57	
b ₁	0.028	0.036	0.71	0.91	
b	0.045	0.055	1.15	1.39	
c	0.014	0.021	0.36	0.53	
D	0.590	0.610	14.99	15.49	
E	0.395	0.410	10.02	10.41	
e		0.100 TYP.		2.54 TYP.	
e ₁		0.200 BSC		5.08 BSC	
F ₁	0.048	0.054	1.22	1.37	
H ₁	0.235	0.255	5.97	6.47	
J ₁	0.100	0.110	2.54	2.79	
L	0.530	0.550	13.47	13.97	
L ₁	0.130	0.150	3.31	3.81	
2					
phi P	0.149	0.153	3.78	3.90	
Q	0.100	0.110	2.54	2.79	

