Absolute Maximum Ratings at T_j=25°C unless otherwise noted

Parameter	Symbol	Value	Unit
Drain-source voltage	V_{DS}	60	V
Gate-source voltage	V_{GS}	±20	V
Continuous drain current[1], T_C=25 °C	I_D	68	A
Pulsed drain current[2], T_C=25 °C	$I_{D,\ pulse}$	204	A
Continuous diode forward current[1], T_C=25 °C	I_S	68	A
Diode pulsed current[2], T_C=25 °C	$I_{S,\ pulse}$	204	A
Power dissipation[3], T_C=25 °C	P_D	81	W
Single pulsed avalanche energy[5]	E_{AS}	91	mJ
Operation and storage temperature	T_{stg}, T_j	-55 to 150	°C

Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal resistance, junction-case	R	1.54	°C/W
Thermal resistance, junction-ambient[4]	R	62	°C/W

Electrical Characteristics at T_j=25°C unless otherwise specified

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Drain-source breakdown voltage	BV_{DSS}	60			V	V_{GS}=0 V, I_D=250 A
Gate threshold voltage	$V_{GS(th)}$	1.0		2.5	V	V_{DS}=V_{GS}, I_D=250 A
Drain-source on-state resistance	$R_{DS(ON)}$		7.5	10		V_{GS}=10 V, I_D=20 A
Drain-source on-state resistance	$R_{DS(ON)}$		10	14		V_{GS}=4.5 V, I_D=10 A
Gate-source leakage current	I_{GSS}			100	nA	V_{GS}=20 V
				-100		V_{GS}=-20 V
Drain-source leakage current	I_{DSS}			1	A	V_{DS}=60 V, V_{GS}=0 V

Oriental Semiconductor © Copyright Reserved V2.0

Dynamic Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Input capacitance	C_{iss}		1204		pF	V_{GS}=0 V, V_{DS}=50 V, Hz
Output capacitance	C_{oss}		194		pF	
Reverse transfer capacitance	C_{rss}		9.9		pF	
Turn-on delay time	$t_{d(on)}$		23.9		ns	V_{GS}=10 V, V_{DS}=50 V, R_G I_D=25 A
Rise time	t_r		4.6		ns	
Turn-off delay time	$t_{d(off)}$		37.8		ns	
Fall time	t_f		6.4		ns	

Gate Charge Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Total gate charge	Q_g		17.9		nC	V_{GS}=10 V, V_{DS}=50 V, I_D=25 A
Gate-source charge	Q_{gs}		3.8		nC	
Gate-drain charge	Q_{gd}		4.2		nC	
Gate plateau voltage	$V_{plateau}$		4.2		V	

Body Diode Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test condition
Diode forward voltage	V_{SD}			1.3	V	I_S=20 A, V_{GS}=0 V
Reverse recovery time	t_{rr}		42.6		ns	V_R=50 V, I_S=25 A,
Reverse recovery charge	Q_{rr}		36.3		nC	
Peak reverse recovery current	I_{rrm}		1.4		A	

Note

1) Calculated continuous current based on maximum allowable junction temperature.
2) Repetitive rating; pulse width limited by max. junction temperature.
3) Pd is based on max. junction temperature, using junction-case thermal resistance.
4) The value of R is measured with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with T_a=25 °C.
5) V_{DD}=30 V,V_{GS}=10 V, L=0.3 mH, starting T_j=25 °C.

Oriental Semiconductor © Copyright Reserved V2.0

Electrical Characteristics Diagrams



Figure 1. Typ. output characteristics



Figure 2. Typ. transfer characteristics



Figure 3. Typ. capacitances



Figure 4. Typ. gate charge

Figure 5. Drain-source breakdown voltage



Figure 6. Drain-source on-state resistance

Oriental Semiconductor © Copyright Reserved V2.0



Figure 7. Threshold voltage



Figure 8. Forward characteristic of body diode

Figure 9. Drain-source on-state resistance



Figure 10. Drain current



Figure 11. Safe operation area T_C=25

Figure 12. Max. transient thermal impedance

Oriental Semiconductor © Copyright Reserved V2.0

Test circuits and waveforms



Figure 1. Gate charge test circuit & waveform



Figure 2. Switching time test circuit & waveforms



Figure 3. Unclamped inductive switching (UIS) test circuit & waveforms



Figure 4. Diode reverse recovery test circuit & waveforms

Package Information



SYMBOL	mm		
	MIN	NOM	MAX
A	0.70	0.80	0.90
A1	0.00	0.03	0.05
b	0.24	0.30	0.35
c	0.10	0.15	0.20
D	3.25	3.32	3.40
D1	3.05	3.15	3.25
D2	2.40	2.50	2.60
E	3.00	3.10	3.20
E1	1.35	1.45	1.55
e	0.65 BSC		
H	3.20	3.30	3.40
L	0.30	0.40	0.50
L1	0.10	0.15	0.20
L2	1.13 REF		

Version 1: PDFN3.3*3.3-K package outline dimension

Oriental Semiconductor © Copyright Reserved V2.0

Ordering Information

Package Type	Units/ Reel	Reels/ Inner Box	Units/ Inner Box	Inner Boxes/ Carton Box	Units/ Carton Box
PDFN3.3*3.3-K	5000	2	10000	6	60000

Product Information

Product	Package	Pb Free	RoHS	Halogen Free
SFS06R10NF	PDFN3.3*3.3	yes	yes	yes

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Oriental Semiconductor hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

For further information on technology, delivery terms and conditions and prices, please contact the Oriental Semiconductor sales representatives (www.orientalsemi.com).

© Oriental Semiconductor Co.,Ltd. All Rights Reserved

ORIENTAL SEMICONDUCTOR