

Electrical Characteristics : $T_c=25^\circ\text{C}$, unless otherwise noted







Parameter	Symbol	Test condition	Min	Typ	Max	Units
OFF						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{\text{GS}} = 0 \text{ V}, I_{\text{D}} = 250 \mu\text{A}$	600	--	--	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{DS}} = 600 \text{ V}, V_{\text{GS}} = 0 \text{ V}$	--	--	1	μA
		$V_{\text{DS}} = 480 \text{ V}, T_c = 125^\circ\text{C}$	--	--	10	μA
Forward Gate-Source Leakage Current	I_{GSSF}	$V_{\text{GS}} = 30 \text{ V}, V_{\text{DS}} = 0 \text{ V}$	--	--	100	μA
Reverse Gate-Source Leakage Current	I_{GSSR}	$V_{\text{GS}} = -30 \text{ V}, V_{\text{DS}} = 0 \text{ V}$	--	--	-100	μA
ON						
Gate Threshold Voltage	$V_{\text{GS(th)}}$	$V_{\text{DS}} = V_{\text{GS}}, I_{\text{D}} = 250 \mu\text{A}$	3	--	5	V
Drain-Source On-Resistance	$R_{\text{DS(on)}}$	$V_{\text{GS}} = 10 \text{ V}, I_{\text{D}} = 2.0 \text{ A}$	--	2.0	2.5	Ω
Forward Transconductance ^(Note 4)	g_{FS}	$V_{\text{DS}} = 30 \text{ V}, I_{\text{D}} = 2.0 \text{ A}$	--	6	--	S
DYNAMIC						
Input Capacitance	C_{iss}	$V_{\text{DS}} = 25 \text{ V}, V_{\text{GS}} = 0 \text{ V}, f = 1.0 \text{ MHz}$	--	545	--	pF
Output Capacitance	C_{oss}		--	61	--	pF
Reverse Transfer Capacitance	C_{rss}		--	10	--	pF
SWITCHING						
Turn-On Delay Time ^(Note 4,5)	$t_{\text{d(on)}}$	$V_{\text{DD}} = 300 \text{ V}, I_{\text{D}} = 4.0 \text{ A}, R_G = 25 \Omega, V_{\text{GS}} = 10 \text{ V}$	--	18	--	ns
Turn-On Rise Time ^(Note 4,5)	t_r		--	27	--	ns
Turn-Off Delay Time ^(Note 4,5)	$t_{\text{d(off)}}$		--	47	--	ns
Turn-Off Fall Time ^(Note 4,5)	t_f		--	21	--	ns
Total Gate Charge ^(Note 4,5)	Q_g	$V_{\text{DS}} = 480 \text{ V}, I_{\text{D}} = 4.0 \text{ A}, V_{\text{GS}} = 10 \text{ V}$	--	12	--	nC
Gate-Source Charge ^(Note 4,5)	Q_{gs}		--	3	--	nC
Gate-Drain Charge ^(Note 4,5)	Q_{gd}		--	6	--	nC
SOURCE DRAIN DIODE						
Maximum Continuous Drain-Source Diode Forward Current	I_S	----	--	--	4	A
Maximum Pulsed Drain-Source Diode Forward Current	I_{SM}	----	--	--	16	A
Drain-Source Diode Forward Voltage	V_{SD}	$V_{\text{GS}} = 0 \text{ V}, I_S = 4.0 \text{ A}$	--	--	1.5	V
Reverse Recovery Time ^(Note 4)	t_{rr}	$V_{\text{GS}} = 0 \text{ V}, I_S = 4.0 \text{ A}$	--	316	--	ns
Reverse Recovery Charge ^(Note 4)	Q_{rr}		$dI_F / dt = 100 \text{ A}/\mu\text{s}$	--	1.2	μC







Note :

1. Repeated rating : Pulse width limited by safe operating area

2. $L=22\text{mH}, I_{AS} = 4.0\text{A}, V_{DD} = 50\text{V}, R_G = 25 \Omega$, Starting $T_J=25^\circ\text{C}$ 3. $I_{SD} = 4.0\text{A}, dI/dt = 100\text{A}/\mu\text{s}, V_{DD} = 50\text{V}, R_G = 25 \Omega$, Starting $T_J=25^\circ\text{C}$


5. Essentially Independent of Operating Temperature Typical Characteristics





TMP4N60AZ(G)**TMPF4N60AZ(G)**

TO-220AB-3L MECHANICAL DATA



SYMBOL	INCHES		MILLIMETERS		NOTES
	MIN.	MAX.	MIN.	MAX.	
A	0.170	0.180	4.32	4.57	
b	~0.028	0.036	0.71	0.91	
b ₁	0.045	0.055	1.15	1.39	
c	~0.014	~0.021	~0.36	0.53	
D	0.590	0.610	14.99	15.49	
E	~0.345	~0.347	10.30	10.41	
e	0.100	TYP.	2.54	TYP.	
e ₁	0.200	BSC	5.08	BSC	
F ₁	~0.048	~0.054	1.22	1.37	
H ₁	0.235	0.255	5.97	6.47	
J ₁	0.100	0.110	2.54	2.79	
L	0.530	0.550	13.47	13.97	
L ₁	0.130	0.150	3.31	3.81	
øP	0.142	~0.153	~3.78	~3.86	
Q	~1.02	~3.12	~26.0	~28.4	

TO-220F-3L MECHANICAL DATA

