


### Features

- 1100V Field Stop Trench Technology
- High Speed Switching
- Low Conduction Loss
- Positive Temperature Coefficient
- Easy Parallel Operation
- RoHS Compliant
- JEDEC Qualification



### Applications

Induction Heating, Soft switching application

Device	Package	Marking	Remark
TGAN40N110FD	TO-3PN	TGAN40N110FD	RoHS

### Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-Emitter Voltage	$V_{CES}$	1100	V
Gate-Emitter Voltage	$V_{GES}$	25	V
Continuous Collector Current	$I_C$	$T_C = 25\text{ }^\circ\text{C}$	80
		$T_C = 100\text{ }^\circ\text{C}$	40
Pulsed Collector Current (Note 1)	$I_{CM}$	120	A
Diode Continuous Forward Current	$I_F$	40	A
Power Dissipation	$P_D$	$T_C = 25\text{ }^\circ\text{C}$	338
		$T_C = 100\text{ }^\circ\text{C}$	135
Operating Junction Temperature	$T_{vj}$	-55 ~ 150	$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55 ~ 150	$^\circ\text{C}$
Maximum lead temperature for soldering purposes,	$T_L$	300	$^\circ\text{C}$

### Thermal Characteristics

Parameter	Symbol	Value	Unit
Maximum Thermal resistance, Junction-to-Case	$R_{JC}$ (IGBT)	0.37	$^\circ\text{C}/\text{W}$
Maximum Thermal resistance, Junction-to-Case	$R_{JC}$ (DIODE)	1.59	$^\circ\text{C}/\text{W}$
Maximum Thermal resistance, Junction-to-Ambient	$R_{JA}$	40	$^\circ\text{C}/\text{W}$

### Electrical Characteristics of the IGBT $T_{vj}=25$ , unless otherwise noted

Parameter	Symbol	Test condition	Min.	Typ.	Max.	Unit
<b>OFF</b>						
Collector Emitter Breakdown Voltage	$BV_{CES}$	$V_{GE} = 0V, I_C = 1mA$	1100	--	--	V
Zero Gate Voltage Collector Current	$I_{CES}$	$V_{CE} = 1100V, V_{GE} = 0V$	--	--	1	mA
Gate Emitter Leakage Current	$I_{GES}$	$V_{CE} = 0V, V_{GE} = \pm 25V$	--	--	$\pm 500$	nA
<b>ON</b>						
Gate Emitter Threshold Voltage	$V_{GE(TH)}$	$V_{GE} = V_{CE}, I_C = 40mA$	3.5	5.5	7.5	V
Collector Emitter Saturation Voltage	$V_{CE(SAT)}$	$V_{GE} = 15V, I_C = 40A, T_{vj} = 25^\circ C$	--	2.0	2.5	V
		$V_{GE} = 15V, I_C = 40A, T_{vj} = 150^\circ C$	--	2.4	--	V
<b>DYNAMIC</b>						
Input Capacitance	$C_{IES}$	$V_{CE} = 30V,$ $V_{GE} = 0V$ $f = 1MHz$	--	4550	--	pF
Output Capacitance	$C_{OES}$		--	110	--	pF
Reverse Transfer Capacitance	$C_{RES}$		--	75	--	pF
<b>SWITCHING</b> (Note 2)						
Turn-On Delay Time	$t_{d(on)}$	$V_{CC} = 600V, I_C = 40A$ $R_G = 10 \Omega, V_{GE} = 15V$ Inductive Load, $T_{vj} = 25^\circ C$	--	45	--	ns
Rise Time	$t_r$		--	75	--	ns
Turn-Off Delay Time	$t_{d(off)}$		--	210	--	ns
Fall Time	$t_f$		--	40	60	ns
Turn-On Switching Loss	$E_{ON}$		--	6.0	9.0	mJ
Turn-Off Switching Loss	$E_{OFF}$		--	1.2	1.8	mJ
Total Switching Loss	$E_{TS}$		--	7.2	10.8	mJ
Turn-On Delay Time	$t_{d(on)}$	$V_{CC} = 600V, I_C = 40A$ $R_G = 10 \Omega, V_{GE} = 15V$ Inductive Load, $T_{vj} = 150^\circ C$	--	40	--	ns
Rise Time	$t_r$		--	65	--	ns
Turn-Off Delay Time	$t_{d(off)}$		--	230	--	ns
Fall Time	$t_f$		--	115	--	ns
Turn-On Switching Loss	$E_{ON}$		--	6.1	9.1	mJ
Turn-Off Switching Loss	$E_{OFF}$		--	1.9	2.8	mJ
Total Switching Loss	$E_{TS}$		--	8.0	11.9	mJ
Total Gate Charge	$Q_g$	$V_{CC} = 600V, I_C = 40A$ $V_{GE} = 15V$	--	210	310	nC
Gate-Emitter Charge	$Q_{ge}$		--	30	45	nC
Gate-Collector Charge	$Q_{gc}$		--	95	140	nC

Not subject to production test verified by design/characterization

**Electrical Characteristics of the DIODE  $T_{vj}=25$  , unless otherwise noted**

Parameter	Symbol	Test condition	Min.	Typ.	Max.	Unit
Diode Forward Voltage	$V_{FM}$	$I_F = 40A, T_{vj} = 25\text{ }^\circ\text{C}$	--	2.3	--	V
		$I_F = 40A, T_{vj} = 150\text{ }^\circ\text{C}$	--	2.5	--	V
Reverse Recovery Time	$t_{rr}$	$I_F = 40A,$ $di/dt = 200A/\mu s,$ $T_{vj} = 25\text{ }^\circ\text{C}$	--	300	--	ns
Reverse Recovery Current	$I_{rr}$		--	30	--	A
Reverse Recovery Charge	$Q_{rr}$		--	5300	--	nC
Reverse Recovery Time	$t_{rr}$	$I_F = 40A,$ $di/dt = 200A/\mu s,$ $T_{vj} = 150\text{ }^\circ\text{C}$	--	380	--	ns
Reverse Recovery Current	$I_{rr}$		--	40	--	A
Reverse Recovery Charge	$Q_{rr}$		--	7540	--	nC

# IGBT Characteristics

Fig. 1 IGBT Output Characteristics




Fig. 2 IGBT Output Characteristics



Fig. 3 IGBT Saturation Voltage vs. Junction Temperature



Fig. 4 IGBT Saturation Voltage vs. Gate Bias




Fig. 5 IGBT Saturation Voltage vs. Gate Bias





Fig. 6 IGBT Capacitance Characteristics



**IGBT Characteristics**

Fig. 7 Turn-on Time vs. Gate Resistor




Fig. 8 Turn-off Time vs. Gate Resistor




Fig. 9 Switching Loss vs. Gate Resistor




Fig. 10 Turn-on Time vs. Collector Current




Fig. 11 Turn-off Time vs. Collector Current





Fig. 12 Switching Loss vs. Collector Current



**IGBT Characteristics**






Fig. 15 RBSOA



Transient Thermal Impedance of IGBT





Fig. 17 Load Current vs. Frequency



## Diode Characteristics

Fig. 18 Diode Conduction Characteristics



Fig. 19 Reverse Recovery Current vs. Forward Current




Fig. 20 Reverse Recovery Charge vs. Forward Current






Fig. 21 Reverse Recovery Time vs. Forward Current



**TO-3PN MECHANICAL DATA**



SYMBOL	MIN	NOM	MAX
A	4.60	4.80	5.00
b	0.80	1.00	1.20
b1	1.80	2.00	2.20
b2	2.80	3.00	3.20
c	0.55	0.60	0.75
c1	1.45	1.50	1.65
D	15.40	15.60	15.80
E	19.70	19.90	20.10
e	5.15	5.45	5.75
L1	3.30	3.50	3.70
L2	19.80	20.00	20.20
φP1	3.30	3.40	3.50
φP2	3.20	3.20	3.20
Q	2.40	2.40	2.60
q1	4.80	5.00	5.20

**Disclaimer**

TRinno technology reserves the right to make changes without notice to products herein to improve reliability, performance, or design. The information given in this document is believed to be accurate and reliable. However, it shall in no event be regarded as a guarantee of conditions and characteristics. With respect to any information regarding the application of the device, TRinno technology hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of patent rights of any third party.