60V N-Ch Power MOSFET

V_{DS}		60	V
$R_{DS(on),typ}$	V_{GS}=10V	7.3	mΩ
$R_{DS(on),typ}$	V_{GS}=4.5V	10	mΩ
$I_{D\ (Sillicon\ Limited)}$		61	A
$I_{D\ (Package\ Limited)}$		40	A





Part Number	Package	Marking
HGI090N06SL	TO-251	GI090N06SL
HGD090N06SL	TO-252	GD090N06SL

Absolute Maximum Ratings at T_j=25℃ (unless otherwise specified)

Parameter	Symbol	Conditions	Value	Unit
Continuous Drain Current (Silicon Limited)	I_D	T_C=25℃	61	A
		T_C=100℃	43	
Continuous Drain Current (Package Limited)		T_C=25℃	40	
Drain to Source Voltage	V_{DS}	-	60	V
Gate to Source Voltage	V_{GS}	-	±20	V
Pulsed Drain Current	I_{DM}	-	270	A
Avalanche Energy, Single Pulse	E_{AS}	L=0.4mH, T_C=25℃	20	mJ
Power Dissipation	P_D	T_C=25℃	75	W
Operating and Storage Temperature	T_J, T_{stg}	-	-55 to175	℃

Absolute Maximum Ratings

Parameter	Symbol	Max	Unit
Thermal Resistance Junction-Ambient	$R_{\theta JA}$	65	℃/W
Thermal Resistance Junction-Case	$R_{\theta JC}$	2	℃/W

Fig 1. Typical Output Characteristics



Figure 2. On-Resistance vs. Gate-Source Voltage



Figure 3. On-Resistance vs. Drain Current and Gate Voltage



Figure 4. Normalized On-Resistance vs. Junction Temperature



Figure 5. Typical Transfer Characteristics



Figure 6. Typical Source-Drain Diode Forward Voltage



Figure 7. Typical Gate-Charge vs. Gate-to-Source Voltage



Figure 8. Typical Capacitance vs. Drain-to-Source Voltage



Figure 9. Maximum Safe Operating Area



Figure 10. Maximun Drain Current vs. Case Temperature

Figure 11. Normalized Maximum Transient Thermal Impedance, Junction-to-Case



Package Outline

TO-251, 3 leads



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.087	0.094
0.018	0.023	c	0.460	0.580
5.460	0.201	0.215	D1	5.100
	0.190 REF.		D2	4.830 REF
6.200	0.236	0.244	E	6.000
2.386	0.086	0.094	e	2.186
11.000	0.409	0.433	L	10.400
	0.138 REF.		L1	3.500 REF
	0.063 REF.		L2	1.600 REF
0.300	0.000	0.012	h	0.000
350 REF.	0.211 REF.		V	5.

TO-252, 2 leads



	Symbol	Min.	Max.	
Max.				
0.094	A	2.200	2.400	0.0
0.005	A1	0.000	0.127	0.0
0.034	b	0.660	0.860	0.0