


**100V N-Ch Power MOSFET**

- ◊
- ◊
- ◊
- ◊
- ◊

$V_{DS}$	100	V
$R_{DS(on),typ}$	$V_{GS}=10V$	8.3
$R_{DS(on),typ}$	$V_{GS}=4.5V$	10.8
$I_D$ (Silicon Limited)	67	A

- ◊
- ◊
- ◊



Part Number	Package	Marking
HGD098N10SL	TO-252	GD098N10SL
HGI098N10SL	TO-251	GI098N10SL







#### Absolute Maximum Ratings at $T_J=25^\circ\text{C}$ (unless otherwise specified)

Parameter	Symbol	Conditions	Value	Unit
Continuous Drain Current (Silicon Limited)	$I_D$	$T_C=25^\circ\text{C}$	67	A
		$T_C=100^\circ\text{C}$	47	
Drain to Source Voltage	$V_{DS}$	-	100	V
Gate to Source Voltage	$V_{GS}$	-	$\pm 20$	V
Pulsed Drain Current	$I_{DM}$	-	160	A
Avalanche Energy, Single Pulse	$E_{AS}$	$L=0.1\text{mH}, T_C=25^\circ\text{C}$	31	mJ
Power Dissipation	$P_D$	$T_C=25^\circ\text{C}$	94	W
Operating and Storage Temperature	$T_J, T_{stg}$	-	-55 to 175	°C

#### Absolute Maximum Ratings


Parameter	Symbol	Max	Unit
Thermal Resistance Junction-Ambient	$R_{JA}$	50	°C/W
Thermal Resistance Junction-Case	$R_{JC}$	1.6	°C/W

Turn on Delay Time	$t_{d(on)}$	-	13	-
		$V_{DD}=50V, I_D=20A, V_{GS}=10V,$	6	-
		$R_G=10 \Omega$	24	-
Fall Time	$t_f$	-	5	-


**Fig 1. Typical Output Characteristics**

**Figure 2. On-Resistance vs. Gate-Source Voltage**

**Figure 3. On-Resistance vs. Drain Current and Gate Voltage**

**Figure 4. Normalized On-Resistance vs. Junction Temperature**

**Figure 5. Typical Transfer Characteristics**

**Figure 6. Typical Source-Drain Diode Forward Voltage**







**Package Outline**
**TO-252, 2 leads**


SYMBOL	DIMENSIONAL REQMTS		
	MIN	NOM	MAX
E	6.40	6.60	6.731
L	1.40	1.52	1.77
L1	2.743	REF	
L2	0.508	BSC	
L3	0.89	--	1.27
L4	0.64	--	1.01
L5	--	--	--
D	6.00	6.10	6.223
H	9.40	10.00	10.40
b	0.64	0.76	0.88
b2	0.77	0.84	1.14
b3	5.21	5.34	5.46
e	2.286	BSC	
A	2.20	2.30	2.38
A1	0	--	0.127
c	0.46	0.50	0.60
c2	0.46	0.50	0.58
ROW	0.10	0.10	0.10
MATRIX L/F	0.10	0.10	0.10
SINGL	0.10	0.10	0.10



**Package Outline**
**TO-251, 3 leads**


SYMBOL	DIMENSIONAL REQMTS		
	MIN	NOM	MAX
E	6.40	6.60	6.731
L	3.98	4.13	4.28
L3	0.89	--	1.27
L4	0.698 REF		
L5	0.972	1.099	1.226
D	6.00	6.10	6.223
H	11.05	11.25	11.45
b	0.64	0.76	0.88
b2	0.77	0.84	1.14
b3	5.21	5.34	5.46
e	2.286 BSC		
A	2.20	2.30	2.38
A1	0.89	1.04	1.15
c	0.46	0.50	0.60
c2	0.46	0.50	0.60
D1	5.10	--	--
E1	4.40	--	--
a	79° REF		